



## GRIP STAR

### Description

GRIP STAR is an agro-industrial tire for loading applications with telehandlers. It shows excellent traction and self-cleaning properties. Besides, it is an all-season tire particularly suitable for operations on muddy ground. GRIP STAR is also available in a "special" version that features extra cut and chip resistance.

### UM

IS Standard

### Construction

⊠ Bias

### Machinery

Industrial & Construction ■ Telehandler



Version	STANDARD
Tire Type	TL
Tyre size	15.5/80-24
LI/SS	

## Dimensions IS Standard

SW (IS) (mm)	392
OD (IS) (mm)	1270
SLR (IS) (mm)	569
RC (IS) (mm)	3683
Rim Rec	W 12
Rim Alt	W 13; W 14 L

## Load Capacity (IS)

km/h / bar	4.00
30 FR LLV	4875
30 DW LLV	3450

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..