



US standard



GROWING TOGETHER

# EARTHMAX

RADIAL OTR TIRES

## SR 35



PRODUCT DATA SHEET



Radial

E-3/L-3

B

214

# EARTHMAX SR 35

RADIAL OTR TIRES



EARTHMAX SR 35 is a low-profile All Steel radial tire specially designed for articulated dump trucks and wheel loaders. It is ideal for operations requiring exceptional traction and flotation. EARTHMAX SR 35 provides both excellent traction and stability. Thanks to its strong steel-belted casing, it ensures extraordinary durability and resistance to snags and punctures. The tire is available as cut-resistant compound for a maximum service life even under severe conditions.

### Technologies



All Steel



Block Pattern

### Performance



Traction



High Load Capacity



Comfort



Durability



Stability



Cut Resistance

	US CODE	Tire size	Type	STAR RATING	LI/SS	Version	TRA CODE	TMPH	O.D.	O.W.	SLR	RC	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	RIM	
									(In.)	(In.)	(In.)	(In.)			Rec.	Alt.
Ø 25"	94058631	650/65 R 25 (25/65 R 25)	TL	**/*	180 B/193 A2	CRC	E-3/L-3	138	59.0	25.0	26.3	176.9	49	776	19.50/2.5	-
	94058587	650/65 R 25 (25/65 R 25)	TL	**	180 B	CRC	E-3	138	59.0	25.0	26.3	176.9	49	776	19.50/2.5	-
	94058624	650/65 R 25 (25/65 R 25)	TL	*	193 A2	CRC	L-3	-	59.0	25.0	26.3	176.9	49	775	19.50/2.5	-
	94053636	750/65 R 25 (30/65 R 25)	TL	**/*	190 B/202 A2	CRC	E-3/L-3	153	63.0	29.1	28.1	189.1	53	963	24.00/3.0	22.00/3.0 ; 25.00/3.0
	94051786	750/65 R 25 (30/65 R 25)	TL	**	190 B	CRC	E-3	153	63.0	29.1	28.1	189.1	53	963	24.00/3.0	22.00/3.0 ; 25.00/3.0
	94071340	750/65 R 25 (30/65 R 25)	TL	**	209 A2	CRC	L-3	-	63.0	29.1	28.1	189.1	53	1007	24.00/3.0	22.00/3.0 ; 25.00/3.0
Ø 29"	94064410	775/65 R 29	TL	**/*	195 B/206 A2	CRC	E-3/L-3	151	69.0	30.5	31.0	209.1	57	1192	24.00/3.5	24.00/3.0 ; 25.00/3.5
	94064427	775/65 R 29	TL	**	195 B	CRC	E-3	151	69.0	30.5	31.0	209.1	57	1192	24.00/3.5	24.00/3.0 ; 25.00/3.5
	94064434	775/65 R 29	TL	*	206 A2	CRC	L-3	-	69.0	30.5	31.0	209.1	57	1192	24.00/3.5	24.00/3.0 ; 25.00/3.5
	94067589	775/65 R 29	TL	**	213 A2	CRC	L-3	-	69.0	30.5	31.0	209.1	57	1296	24.00/3.5	24.00/3.0 ; 25.00/3.5
	94059812	875/65 R 29 (35/65 R 29)	TL	**/*	203 B/214 A2	CRC	E-3/L-3	191	73.2	35.0	32.1	218.9	60	1506	27.00/3.50	27.00/3.0 ; 28.00/3.5
	94059805	875/65 R 29 (35/65 R 29)	TL	**	203 B	CRC	E-3	191	73.2	35.0	32.1	218.9	60	1506	27.00/3.50	27.00/3.0 ; 28.00/3.5
94059836	875/65 R 29 (35/65 R 29)	TL	*	214 A2	CRC	L-3	-	73.2	35.0	32.1	218.9	60	1506	27.00/3.50	27.00/3.0 ; 28.00/3.5	

CRC: Cut Resistance Compound



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference