



IS standard

BKT

GROWING TOGETHER

AW 705



ÜRÜN VERİ SAYFASI



Çift Yönlü



Performans



Dayanıklılık



Yüksek Yük Kapasitesi



	Lastik ebadı	JANT		K.E. (mm)	T.Ç. (mm)	SYY (mm)	ÇU (mm)	Sürüm	PR	Tip	LI/SS	
		Önr.	Alt.								DW	FR
Ø 20"	16.0/70 - 20	13.0	12 SDC ; 13 SDC ; 14	408	1075	480	3155	SPL	14	TL	-	154 A8
	16.0/70 - 20	13.0	12 SDC ; 13 SDC ; 14	408	1075	480	3155	STD	14	TL	-	154 A8
	16.0/70 - 20	13.0	12 SDC ; 13 SDC ; 14	408	1075	480	3155	STD	16	TL	-	156 A8
Ø 22.5"	400/55 - 22.5	AG 11.75	12.25 ; AG 13.00	405	1016	443	3072	STD	18	TL	-	154 A8
	400/55 - 22.5	AG 11.75	12.25 ; AG 13.00	405	1016	443	3072	SR	20	TL	-	156 A8

STD: Standart - SR: Anıza dayanıklı - SPL: Özel



Toleranslar: T.Ç. ± 2% - K.E. ± 2% - ÇU ± 2,5% - LI/SS = Yük Endeksi / Hız Sembölü; K.E. = Kesit Eni;
T.Ç. = Toplam Çap; SYY = Sabit Yüklü Yarıçap; ÇU = Çevresel Uzunluk; DW = Tahrik Tekerleği; FR = Serbest Dönen