



TR 273

Description

TR 273 is a tractor tire suitable for soil tillage and specifically designed to provide maximum performance on wet and moist soil. In these soil conditions, a tire is required to offer superior grip and enhanced self-cleaning properties. TR 273 perfectly meets all these characteristics.

UM

IS Standard

Construction

◇◇ Bias

Machinery

Agriculture ▪ Tractor



| | |
|-----------|----------|
| Version | STANDARD |
| Tire Type | TT |
| Tyre size | 23.1-34 |
| LI/SS | 160;A6 |

Dimensions IS Standard

| | |
|---------------|------------------|
| SW (IS) (mm) | 590 |
| OD (IS) (mm) | 1850 |
| SLR (IS) (mm) | 831 |
| RC (IS) (mm) | 5674 |
| Rim Rec | DW 20 A; DW 20 B |
| ECE | E11-106R-003646 |
| TRA Code | R2 |

Load Capacity (IS)

| | |
|------------|------|
| km/h / bar | 2.00 |
| 30 | 4500 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..