



IS standard



GROWING TOGETHER

# EARTHMAX

RADIAL OTR TIRES

## SR 44



PRODUCT DATA SHEET



Radial



Technologies



All Steel

Performance



Durability



High Load Capacity



Comfort



# EARTHMAX SR 44

RADIAL OTR TIRES

EARTHMAX SR 44 is an *All Steel* radial tire suitable for a variety of applications including mining, haulage and logging applications. The rugged E-4 tread pattern provides both excellent traction and operator comfort. EARTHMAX SR 44 (E-4) is able to optimize productivity whatever your operation is.

	Tire size	Type	TRA CODE	STAR RATING	LI/SS	Version	TKPH	O.W.	O.D.	SLR	RC	TREAD DEPTH (mm)	RIM		
								(mm)	(mm)	(mm)	(mm)		Rec.	Alt.	
Ø 16"	7.50 R 16	TT	-	-	122/118 G	STD	-	226	820	380	2450	19	6	5.5 ; 6.5	
	Ø 20"	10.00 R 20	TT	-	-	146/143 G	STD	-	268	1075	505	3200	25	7.50	7.0 ; 7.50 VM ; 8.0
		11.00 R 20	TT	E-4	***	-	STD	-	282	1111	520	3328	25	8.00	7.50 ; 8.50 ; 8.50 VM
	12.00 R 20	TT	E-4	***	-	STD	-	305	1138	532	3408	25	8.50 V	9.00 V	
Ø 24"	12.00 R 24	TT	E-4	***	158 B	STD	140	310	1250	575	3790	30	8.50 V	9.00 V	
	325/95 R 24	TT	E-4	***	158 B	STD	140	310	1250	575	3790	30	8.50 V	9.00 V	
	325/95 R 24	TL	E-4	***	158 B	STD	140	310	1250	575	3790	30	8.50 V	9.00 V	

STD: Standard



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference