



US standard



GROWING TOGETHER

TR 137



PRODUCT DATA SHEET



Bias



Technologies



Aramid Belted



Heavy Duty

Performance



High Load Capacity



Traction



Durability



Self-Cleaning



Stubble Resistance



Cut and Chip Resistance



TR 137

TR 137 is BKT's most suitable tire for all harvesting operations. It ensures excellent traction in the fields even with high loads. The tire is available in different versions: the "aramid-belted" version provides better puncture resistance and protection against all typical damages of this application; the "HD" version provides extraordinary cut and chip resistance, and an extended tire life-cycle.

	US CODE	Tire size	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version	PR	Type	LI/SS
			Rec.	Alt.										
Ø 32"	94004317	24.5 - 32	DW 21 B	DW 20 B	24.5	71.1	31.8	210.4	52	489	STD	12	TL	156A8
	94004324	24.5 - 32	DW 21 B	DW 20 B	24.5	71.1	31.8	210.4	52	486	STD	14	TL	159A8
	94004331	30.5 L - 32	DH 27 B	DW 27 B	30.3	73.4	32.7	217.3	60	626	STD	12	TL	158A8
	94039913	30.5 L - 32	DH 27 B	DW 27 B	30.3	73.4	32.7	217.3	60	626	STD	14	TL	160A8
	94004348	30.5 L - 32	DH 27 B	DW 27 B	30.3	73.4	32.7	217.3	60	661	STD	16	TL	164A8
	94002986	30.5 L - 32	DH 27 B	DW 27 B	30.3	73.4	32.7	217.3	60	673	AB	18	TL	167A8
	94004355	30.5 L - 32	DH 27 B	DW 27 B	30.3	73.4	32.7	217.3	60	657	HD	18	TL	167A8

STD: Standard - AB: Aramid Belted - HD: Heavy Duty



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference