



AGRIMAX PROHARVEST



AGRIMAX PROHARVEST is BKT's response to the current market needs in terms of combines and harvesting machines. The advanced VF (Very High Flexion) technology allows AGRIMAX PROHARVEST to carry 40% more load compared to standard tyres with the same tyre pressure minimizing soil compaction. Moreover, the three layers of steel belts combined with the cut and chip resistant compound ensure excellent puncture resistance, even on case of stubbles or crops leftovers on the field. The structure of the tyre with a reinforced bead and a strong polyester carcass is synonym of durability and stability of the tyre even during heavy duty operation.

IS Standard

 Radial

Agriculture ■ Harvester

STEEL BELTED

TL

VF900/60R32

193;D

undefined IS Standard

881

1900

837

5712

DW 30 B

E11-106R-0010580

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2
70	4085	4710	5340	6070	6700	7435	8270	8375	9735	10465
from										
65 to	4485	5175	5865	6670	7360	8165	9085	9200	10695	11500
40										
30	4575	5280	5985	6805	7510	8330	9270	9385	10910	11730
20	4665	5385	6100	6940	7655	8495	9450	9570	11125	11960
10	4935	5695	6455	7340	8100	8985	9995	10120	11765	12650
Upto										
30	5095	5875	6660	7575	8360	9270	10315	10445	12145	13055
Cyc										
Upto										
15	6080	7015	7950	9040	9975	11070	12315	12470	14495	15585
Cyc										
Upto										
10	6665	7690	8715	9910	10935	12130	13495	13665	15885	17080
Cyc										
10HT	4575	5280	5985	6805	7510	8330	9270	9385	10910	11730

25-02-2026