



FL 695

Description

FL 695 has been specifically designed for tra and farming transport applications with a un pattern. Thanks to its strong casing, FL 695 c maintaining stability in all conditions. Its deep self-cleaning during on-and-off-the-road ap steel-cord layers reinforce this pattern again

UM

US Standard

Construction

 Radial

Machinery

Agriculture ■ Trailer, Industrial & Construction



Version

STEEL BELTED

Tire Type

TL

Tyre size

600/60R30.5

LI/SS

179;D

Dimensions US Standard

USA Code	94073832
SW (US) (in)	24.1
OD (US) (in)	58.9
SLR (US) (in)	27.3
RC (US) (in)	180.6
Rim Rec	AG20.00
ECE	E11-106R-008503

Load Capacity (US)

mph / psi	12	17	23	29	35	41	46	52	58	65	73
40	--	--	--	7690	8880	10090	11110	12140	13330	14190	15030
30	--	--	--	9310	10760	12200	13450	14680	16140	17170	18200
25	--	7670	9530	10460	12090	13710	15110	16500	18130	19290	20600
20	6460	8520	10580	11620	13430	15230	16780	18330	20130	21430	22720
15	6760	8920	11080	12160	14040	15930	17550	19170	21060	22410	23760
10	7050	9310	11560	12700	14670	16640	18330	20030	22000	23410	24820
5	7690	10150	12610	13840	15990	17280	18150	19990	21840	24000	27070

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different L condition.

Printed on 24-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic form or otherwise without prior written consent by Balkrishna Industries Ltd..