



## FL 695

### Description

FL 695 has been specifically designed for trailers in construction and farming transport applications with a unique center-block tread pattern. Thanks to its strong casing, FL 695 can carry heavy loads maintaining stability in all conditions. Its deep tread ensures optimal self-cleaning during on-and-off-the-road applications. Multiple steel-cord layers reinforce this pattern against punctures.

### UM

US Standard

### Construction

 Radial

### Machinery

Agriculture ■ Trailer, Industrial & Construction ■ Trailer



|           |              |
|-----------|--------------|
| Version   | STEEL BELTED |
| Tire Type | TL           |
| Tyre size | 600/60R30.5  |
| LI/SS     | 179;D        |

## Dimensions US Standard

|               |                 |
|---------------|-----------------|
| USA Code      | 94073832        |
| SW (US) (in)  | 24.1            |
| OD (US) (in)  | 58.9            |
| SLR (US) (in) | 27.3            |
| RC (US) (in)  | 180.6           |
| Rim Rec       | AG20.00         |
| ECE           | E11-106R-008503 |

## Load Capacity (US)

| mph / psi | 12   | 17    | 23    | 29    | 35    | 41    | 46    | 52    | 58    | 65    | 73    | 80    | 87    |
|-----------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 40        | --   | --    | --    | 7690  | 8880  | 10090 | 11110 | 12140 | 13330 | 14190 | 15030 | 16060 | 17080 |
| 30        | --   | --    | --    | 9310  | 10760 | 12200 | 13450 | 14680 | 16140 | 17170 | 18200 | 19440 | 20680 |
| 25        | --   | 7670  | 9530  | 10460 | 12090 | 13710 | 15110 | 16500 | 18130 | 19290 | 2060  | 21850 | 23240 |
| 20        | 6460 | 8520  | 10580 | 11620 | 13430 | 15230 | 16780 | 18330 | 20130 | 21430 | 22720 | 24260 | 25800 |
| 15        | 6760 | 8920  | 11080 | 12160 | 14040 | 15930 | 17550 | 19170 | 21060 | 22410 | 23760 | 25380 | 26990 |
| 10        | 7050 | 9310  | 11560 | 12700 | 14670 | 16640 | 18330 | 20030 | 22000 | 23410 | 24820 | 26510 | 28200 |
| 5         | 7690 | 10150 | 12610 | 13840 | 15990 | 17280 | 18150 | 19990 | 21840 | 24000 | 27070 | 28910 | 30750 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..