



FLOTATION 648



Description

FLOTATION 648 is particularly suitable for field and road transport as well as for spreading operations. Some sizes are designed for hay harvesters/balers. The special tread design allows for carrying very heavy loads at low pressure, guaranteeing at the same time reduced soil compaction and preventing damage to crops.

UM

US Standard

Construction

◆ Bias

Machinery

Agriculture ■

Version	DUAL BEAD
Tyre Type	TL
Tyre size	600/50-22.5
LI/SS	

Dimensions US Standard

USA Code	94045266
SW (in)	24.1
OD (in)	46.1
SLR (in)	20.1
RC (in)	137.8
Rim Rec	AG 20.00
ECE	E11-106R-004392

Load Capacity (US)

mph / psi	44	45	46
5 FR	17240	17580	17900
10 FR	15510	15820	16110
20 FR	13790	14060	14320
25 FR	12310	12550	12790
30 FR	11080	11300	11350
5 DW	11880	12110	12350
10 DW	10690	10900	11110
20 DW	9500	9690	9880
25 DW	8490	8650	8820
30 DW	7640	7790	7830

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21-03-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..