



## MAGLIFT SMOOTH

### Description

MAGLIFT SMOOTH has been particularly designed for ground support equipment (GSE), port and industrial trailers operating on smooth surfaces. The tire is made of a special tread compound which ensures excellent cut and chip resistance. The smooth tread design provided extraordinary stability and optimized load distribution even under heavy-duty service conditions. The tire stands for excellent traction, low rolling resistance and low heat built up for improved efficiency.



### UM

IS Standard

### Construction

 Solid

### Machinery

Industrial & Construction ■ Trailer

Version

STANDARD

Tyre size

10.00-20

LI/SS

## Dimensions IS Standard

OD (IS) (mm)	1015
Rim Rec	7.50 - 20

## Load Capacity (IS)

km/h / bar	-
25 LOAD WHEEL	6000
25 STEER WHEEL	5000
10 OTHER VEHICLES	5450

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..