



## RIB 324

### Description

RIB 324 has been designed with a special block tread pattern and a large contact area to provide best stability and flotation features on loose soil and sandy terrain. The strong nylon casing and sidewall along with a special tread compound stand for excellent resistance against punctures and wear as well as higher load capacity.

### UM

US Standard

### Construction

 Bias

### Machinery

Agriculture ▪ Implement Machinery, Industrial & Construction ▪ Trailer



Version	STANDARD
Tire Type	TL
Tyre size	66x44.00-25
LI/SS	

## Dimensions US Standard

USA Code	94064274
SW (US) (in)	43.7
OD (US) (in)	66.9
Rim Rec	36.0 TH

## Load Capacity (US)

mph / psi	50
30	16090

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..