



CRANE SPECIAL



Description

CRANE SPECIAL is suitable for pick & carry cranes on rough terrains. The tire is made of a special compound which provides high stability and durability.

UM

US Standard

Construction

⌘ Bias

Machinery

Industrial & Construction ■ Mobile Crane

Version	STANDARD
Tire Type	TT
Tyre size	16.00-25
LI/SS	

Dimensions US Standard

USA Code	94041541
OD (US) (in)	58.5
SLR (US) (in)	26.9
RC (US) (in)	173.0
Rim Rec	11.25/2.0
TRA Code	E3

Load Capacity (US)

mph / psi	83
30	14800

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 24-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..