



IS standard



GROWING TOGETHER

COMMANDER (R)



PRODUCT DATA SHEET



Bias



Technologies



Extra Deep Tread

Performance



Cut and Chip Resistance



Durability



High Load Capacity



Self-Cleaning



Traction



COMMANDER (R)

🇬🇧 COMMANDER (R) is an agricultural tyre featuring a deep tread with strong lug bases for a longer tyre life-cycle. The special dual-angle lug design provides excellent traction in the fields and top self-cleaning properties. The strong casing is made of a cut-and-chip-resistant compound providing better puncture resistance together with high load capacity. COMMANDER (R) is the perfect tyre for soil tillage, haulage and harvesting operations.

	Tyre size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 20"	9.5 - 20	W 8	W 7	245	970	456	2949	STD	12	TT	109 A6
	Ø 24"	9.5 - 24	W 8	W 7	245	1065	507	3308	STD	12	TT
	11.2 - 24	W 10	W 9	295	1125	533	3483	STD	12	TT	123 A6
	12.4 - 24	W 11	W 10	328	1180	569	3669	STD	12	TT	128 A6
	12.4 - 24	W 11	W 10	328	1180	569	3669	STD	8	TT	121 A6
Ø 28"	12.4 - 28	W 11	W 9 ; W 10	320	1285	600	3946	STD	12	TT	125 A6
	13.6 - 28	W 12	W 11	360	1345	623	4068	STD	12	TT	128 A6
	14.9 - 28	W 13	W 11 ; W 12	388	1380	642	4176	STD	12	TT	134 A6
	15.9 - 28	W 13	W 11 ; W 12	405	1410	654	4280	STD	12	TT	140 A6
	16.9 - 28	W 15 L	W 14 L	440	1435	663	4274	STD	12	TT	143 A6
	16.9 - 28 (21L)	W 15 L	W 14 L	440	1435	-	-	STD	12	TT	143 A6
	17.9 - 28	W 15 L	W 14 L	458	1515	-	-	STD	12	TT	144 A6
	Ø 30"	16.9 - 30	W 15 L	W 14 L	440	1480	689	4537	STD	12	TT
18.4 - 30		W 16 L	-	472	1565	734	4834	STD	14	TT	151 A6

STD: Standard

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference



Bias



A6



Technologies



Extra Deep Tread

Performance



Cut and Chip Resistance



Durability



High Load Capacity



Self-Cleaning



Traction



	Tyre size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 30"	18.4 - 30	W 16 L	-	472	1565	734	4834	STD	18	TL	155 A6
	18.4 - 30	W 16 L	-	472	1565	734	4834	STD	18	TT	155 A6
	18.4 - 30	W 16 L	-	472	1565	734	4834	STD	8	TT	139 A6
Ø 36"	9.5 - 36	W 8	W 7	246	1376	-	-	STD	12	TT	126 A6

STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference