



RIDEMAX FROST

Description

RIDEMAX FROST is engineered by BKT for tractors operating in transport and municipal maintenance during snow and ice conditions. With a cold-resistant, specially formulated compound, the tire maintains flexibility and elasticity even at sub-zero temperatures, ensuring optimal grip in extreme winter environments. The tread, featuring multiple sipes, delivers excellent traction on snowy and icy surfaces, creating micro-edges and partial vacuum in the slit that improve grip and reduce the risk of slippage. Additionally, the tread design incorporates snow, utilizing snow-to-snow adhesion to further enhance traction.



UM

US Standard

Construction

 Radial

Machinery

Agriculture ■ Tractor

| | |
|-----------|--------------|
| Version | STEEL BELTED |
| Tire Type | TL |
| Tyre size | 440/80R28IND |
| LI/SS | 156;A8 |

Dimensions US Standard

| | |
|---------------|------------------|
| USA Code | 94513338 |
| SW (US) (in) | 17.4 |
| OD (US) (in) | 55.9 |
| SLR (US) (in) | 25.3 |
| RC (US) (in) | 169.1 |
| Rim Rec | DW 14 L |
| Rim Alt | DW 15 L |
| ECE | E11-106R-0010949 |

Load Capacity (US)

| mph / psi | 12 | 17 | 23 | 29 | 35 | 38 | 41 | 44 | 46 |
|-----------|------|------|------|------|-------|-------|-------|-------|-------|
| 45 | 3350 | 4420 | 5320 | 5860 | 6240 | 6550 | 6840 | 7230 | 7610 |
| 30 | 3630 | 4770 | 5760 | 6340 | 6750 | 7080 | 7410 | 7810 | 8220 |
| 25 | 3880 | 5110 | 6170 | 6790 | 7230 | 7580 | 7940 | 8380 | 8820 |
| 20 | 4020 | 5300 | 6390 | 7030 | 7480 | 7860 | 8220 | 8670 | 9130 |
| 10 | 4220 | 5570 | 6710 | 7390 | 7870 | 8260 | 8630 | 9120 | 9590 |
| 5 | 4830 | 6360 | 7670 | 8440 | 8990 | 9420 | 9870 | 10420 | 10960 |
| 3 | 5600 | 7370 | 8910 | 9790 | 10430 | 10930 | 11440 | 12080 | 12710 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..