



AGRIMAX SIRIO



Description

AGRIMAX SIRIO is a high-speed tire (up to 70 km/h - 45 mph) developed for high-performance tractors. Its design is perfect for both haulage and soil tillage applications. The high sidewall flexibility ensures outstanding stability, handling and comfort to improve the driving experience. It is also available with IF technology that allows to carry heavy loads at a low inflating pressure. The reinforced casing and the high number of belts guarantee great traction on the field.

UM

IS Standard

Construction

 Radial

Machinery

Agriculture ■ High-Power Tractor

Version HIGH SPEED

Tire Type TL

Tyre size 540/65R30

LI/SS 150;D

Dimensions IS Standard

SW (IS) (mm)	530
OD (IS) (mm)	1464
SLR (IS) (mm)	669
RC (IS) (mm)	4400
Rim Rec	W 16 L
Rim Alt	W 18
ECE	E4-106R-000814
TRA Code	R1W

Load Capacity (IS)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
70	1450	1665	1910	2155	2400	2645	2860	3075
65	1575	1810	2080	2345	2615	2885	3120	3350
50	1655	1905	2185	2465	3750	3030	3275	3520
40	1725	1985	2280	2570	2865	3160	3415	3670
25	1870	2145	2465	2780	3100	3415	3695	3970
10	2365	2715	3120	3520	3920	4325	4675	5025

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..