



US standard



GROWING TOGETHER

# RIDEMAX

RADIAL TRANSPORT TIRES

## FL 693 M



PRODUCT DATA SHEET



Radial



# RIDE MAX FL 693 M

RADIAL TRANSPORT TIRES

RIDE MAX FL 693 M is the ideal radial tire for those who frequently travel on the road with trailers/tank trucks. Actually designed for 75% on-the-road use, RIDE MAX FL 693 M provides excellent road performance prioritizing both comfort and self-cleaning properties. The speed index classes D/E of the range stands for higher speeds when travelling on the road leading to significant time savings. The low rolling resistance contributes to less fuel consumption, while a reinforced bead and steel belts ensure enhanced durability.

### Technologies



Steel Belted



Reinforced Bead



High Speed



Block Pattern

### Performance



Road Oriented



Durability



Fuel Economy



Self-Cleaning

	US CODE	Tire size	LI/SS	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version
				Rec.	Alt.							
Ø 17"	94059324	425/55 R 17	129 D/ 140 A8	13.00	-	16.5	35.2	15.6	106.5	18	108	STD
	94045181	500/50 R 17	149 D/ 146 E	16.00	-	19.8	36.7	16.7	114.7	19	128	STD
	94069453	VF 500/50 R 17	156 D	16.00	-	19.8	36.7	16.6	113.4	19	138	STD
Ø 17.5"	94066063	400/45 R 17.5	139 D	14.00	-	15.7	31.5	13.5	92.8	14	87	STD
	94069323	VF 400/45 R 17.5	142 D	14.00	-	15.7	31.5	14.1	96.4	14	88	STD
Ø 22.5"	94043767	500/45 R 22.5	146 D/ 143 E	AG 16.00	-	19.8	40.2	17.9	122.6	26	179	STD
	94040605	500/60 R 22.5	155 D/ 152 E	AG 16.00	15.00 ; 17.00	19.8	46.1	20.9	140.8	26	223	STD
	94069446	500/60 R 22.5	163 D	AG 16.00	15.00 ; 17.00	19.8	46.1	21.4	142.7	26	241	STD
	94037322	560/45 R 22.5	152 D/ 149 E	AG 16.00	-	21.4	42.4	19.3	130.2	26	218	STD
	94075225	560/45 R 22.5	160 D	AG 16.00	-	21.4	42.4	19.3	130.2	26	240	STD
	94037353	560/55 R 22.5	158 D/ 155 E	AG 16.00	17.00 ; 20.00	21.4	46.5	21.0	142.3	26	235	STD
	94067626	560/55 R 22.5	162 D	AG 16.00	17.00 ; 20.00	21.4	46.5	21.0	142.3	26	236	STD
	94037247	560/60 R 22.5	161 D/ 158 E	AG 16.00	16.00 ; 17.00 ; AG 20.00	21.4	49.0	21.6	148.3	26	255	STD
	94045891	560/60 R 22.5	165 D/ 162 E	AG 16.00	16.00 ; 17.00 ; AG 20.00	21.4	49.0	21.7	148.3	26	256	STD

STD: Standard

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference



Radial



Technologies



Steel Belted



Reinforced Bead



High Speed



Block Pattern

Performance



Road Oriented



Durability



Fuel Economy



Self-Cleaning

	US CODE	Tire size	LI/SS	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version
				Rec.	Alt.							
Ø 22.5"	94066193	560/60 R 22.5	169 D	AG 16.00	16.00 ; 17.00 ; AG 20.00	21.4	49.0	21.7	148.3	26	293	STD
	94037254	580/65 R 22.5	166 D/ 163 E	AG 18.00	AG 16.00 ; AG 17.00 ; AG 20.00	22.7	52.2	22.5	158.7	26	281	STD
	94037032	600/50 R 22.5	159 D/ 156 E	AG 20.00	-	24.1	46.1	20.3	140.7	26	251	STD
	94043019	650/50 R 22.5	163 D/ 160 E	AG 20.00	-	25.4	48.1	21.1	146.3	26	279	STD
	94055654	650/50 R 22.5	168 D	AG 20.00	-	25.4	48.1	21.1	146.3	26	278	STD
	94056132	710/35 R 22.5	157 D/ 154 E	AG 24.00	-	28.0	42.1	19.0	128.1	28	251	STD
	94062447	710/45 R 22.5	165 D	AG 24.00	-	27.8	47.7	21.3	144.0	28	292	STD
Ø 26.5"	94047277	600/55 R 26.5	165 D	AG 20.00	-	24.1	52.5	23.1	159.5	30	315	STD
	94049615	600/55 R 26.5	177 D	AG 20.00	-	24.1	52.5	23.1	160.5	30	326	HD
	94037537	650/55 R 26.5	169 D	AG 20.00	-	25.4	54.7	24.4	166.0	30	346	STD
	94049622	650/55 R 26.5	178 D	AG 20.00	-	25.4	54.7	24.2	167.3	30	356	HD
	94037315	710/50 R 26.5	170 D	AG 24.00	AG 20.00	28.6	54.4	24.6	166.0	30	372	STD
	94063673	710/50 R 26.5	179 D	AG 24.00	AG 20.00	28.6	54.4	23.9	166.0	30	381	HD
Ø 30.5"	94064335	600/60 R 30.5	169 D	AG 20.00	AG 18.00	23.8	58.9	26.8	177.0	30	374	STD

STD: Standard - HD: Heavy Duty

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference



Radial



Technologies



Steel Belted



Reinforced Bead



High Speed



Block Pattern

Performance



Road Oriented



Durability



Fuel Economy



Self-Cleaning



	US CODE	Tire size	LI/SS	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version
				Rec.	Alt.							
Ø 30.5"	94069330	600/60 R 30.5	173 D	AG 20.00	AG 18.00	23.8	58.9	26.8	177.0	30	388	STD
	94075324	650/65 R 30.5	176 D	AG 20.00	-	25.4	63.9	28.9	194.4	31	435	STD
	94037049	710/50 R 30.5	173 D	AG 24.00	AG 20.00	28.6	58.5	26.6	178.5	32	425	STD
	94033812	750/60 R 30.5	181 D	AG 24.00	-	29.7	65.9	28.7	200.5	32	545	STD
	94034505	850/50 R 30.5	182 D	AG 28.00	-	33.9	64.0	28.3	193.9	32	592	STD

STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference