



IS standard



GROWING TOGETHER

SIERRAMAX

ATV & GO KART TIRES

PRO



PRODUCT DATA SHEET



Radial



56

Technologies



Larger Footprint

Performance



Handling and Comfort



Traction



Stability



Steering Control



SIERRA MAX PRO
ATV & GO KART TIRES

SIERRA MAX PRO is the perfect BKT tire for all-terrain vehicles in ATV applications, also including side-by-side racing. Its radial construction and special wider footprint area provide a smoother ride and an optimized lateral as well as forward traction. Special sturdy lugs have been studied specifically to provide excellent traction and firm grip on the terrain. These features ensure an extraordinarily comfortable ride providing safety and driving control. SIERRA MAX PRO provides excellent performance on every kind of terrain, from hardpack terrains to loose soils.

	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
Ø 12"	AT 25 X 8 R 12	43 N	6.5	-	200	630	287	1860	-	STD
	AT 25 X 10 R 12	50 N	8.0	-	260	635	293	1897	-	STD
	NEWSIZE									
Ø 14"	AT 27 X 11 R 14	56 N	9.00	-	285	708	336	2145	-	STD

STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; SRI = Speed Radius Index