



IS standard



GROWING TOGETHER

# CONTAINER KING



PRODUCT DATA SHEET



Bias



Performance



Stability



Durability



# CONTAINER KING

🇬🇧 CONTAINER KING has been designed for reach stackers in intermodal transport and logistics applications. This extraordinary tire is made of a highly wear-and-tear-resistant tread compound which minimizes tread cracks. CONTAINER KING ensures an extended tire life-cycle plus exceptional stability in lift mode.

|       | Tire size  | Type | PR | LI/SS | Version | O.W.<br>(mm) | O.D.<br>(mm) | SLR<br>(mm) | RC<br>(mm) | TREAD<br>DEPTH<br>(mm) | RIM       |           |
|-------|------------|------|----|-------|---------|--------------|--------------|-------------|------------|------------------------|-----------|-----------|
|       |            |      |    |       |         |              |              |             |            |                        | Rec.      | Alt.      |
| Ø 24" | 12.00 - 24 | TT   | 24 | -     | IND     | 330          | 1285         | -           | -          | 33.5                   | 8.5       | 8.0       |
| Ø 25" | 18.00 - 25 | TL   | 40 | -     | IND     | 528          | 1675         | 765         | 4955       | 67.5                   | 13.00/2.5 | 15.00/2.5 |
| Ø 33" | 18.00 - 33 | TL   | 40 | -     | IND     | 510          | 1895         | 852         | 5820       | 67.5                   | 13.00/2.5 | -         |

IND: Industrial



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference