



## FARM SPECIAL

### Description

FARM SPECIAL is a tractor tire suitable for soil tillage operations. The strong casing provides a high level of puncture resistance and a longer service life, whilst the rounded shoulders prevent soil damages ensuring the protection of the valuable crops. FARM SPECIAL features a unique tread design with special mud breakers for best self-cleaning properties. In addition, dual angled lugs provide excellent traction and reduced slippage.



### UM

US Standard

### Construction

◆ Bias

### Machinery

Agriculture ■ Tractor

Version	STANDARD
Tire Type	TT
Tyre size	14.9-24
LI/SS	124;A8

## Dimensions US Standard

USA Code	94060719
SW (US) (in)	14.9
OD (US) (in)	49.4
SLR (US) (in)	22.5
RC (US) (in)	148.6
Rim Rec	W 13
Rim Alt	W 11; W 12
ECE	E11-106R-005531
TRA Code	R1

## Load Capacity (US)

mph / psi	26
25	3520

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..