



## FARM 2000



### Description

The FARM 2000 tire is suitable on tractors for soil tillage and transport applications. It is the ideal tire for heavy-duty use and in all operating conditions where good traction is required.

### UM

US Standard

### Construction

◆ Bias

### Machinery

Agriculture ▪ Tractor

Version STANDARD

Tire Type TT

Tyre size 250/80-18

LI/SS

## Dimensions US Standard

USA Code	94040285
SW (US) (in)	9.4
OD (US) (in)	34.3
SLR (US) (in)	15.5
RC (US) (in)	105.5
Rim Rec	W 8
Rim Alt	W7; W9
ECE	E11-106R-003519
TRA Code	R1

## Load Capacity (US)

mph / psi	41
5 FR	5400
15 FR	4600
20 FR	4320
25 FR	3860
5 DW	3750
15 DW	3190
20 DW	3000
25 DW	2680

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 24-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..