



IS standard



GROWING TOGETHER

# FLOTATION 648 T



PRODUCT DATA SHEET



Bias



166

Performance



Durability



High Load Capacity



Traction



# FLOTATION 648 T

FLOTATION 648 T is particularly suitable for hay harvesting as well as for field and road transport. The special tread design allows for carrying very heavy loads at low pressure and ensures outstanding self-cleaning properties. The tire also stands for excellent traction and durability.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS	
		Rec.	Alt.								DW	FR
Ø 22.5"	550/45 - 22.5	AG 16.00	-	550	1070	475	3203	STD	16	TL	147 A8/ 144 B	159 A8/ 156 B
	550/45 - 22.5	AG 16.00	-	550	1070	475	3203	STD	20	TL	154 A8/ 150 B	166 A8/ 162 B

STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; DW = Drive Wheel; FR = Free Rolling