



TR 126

Description

TR 126 is designed to fit small tractors in soil tillage operations. The deep lugs and the tread pattern provide excellent traction and outstanding load capacity features providing best tire performance in all operating conditions.

UM

IS Standard

Construction

⊠ Bias

Machinery

Agriculture ■ Small Tractor



Version	HD
Tire Type	TT
Tyre size	7-14
LI/SS	80;A6

Dimensions IS Standard

SW (IS) (mm)	157
OD (IS) (mm)	655
SLR (IS) (mm)	305
RC (IS) (mm)	1978
Rim Rec	5 JA; 5 KB
ECE	E11-106R-007418
TRA Code	R1

Load Capacity (IS)

km/h / bar	04:25:00																		
30	450																		

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 24-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..