



IS standard



GROWING TOGETHER

# AW 705



PRODUCT DATA SHEET



Bias



A8



156

## Performance



Durability



High Load Capacity



# AW 705

AW 705 has been developed for implement machinery, trailers and balers in soil tillage and haulage applications. It is ideal for modern farming thanks to improved durability and high load capacity.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS	
		Rec.	Alt.								DW	FR
Ø 16"	14.0/65 - 16	11.0	-	353	870	388	2549	STD	14	TT	-	142 A8
	14.0/65 - 16	11.0	-	353	870	388	2549	STD	10	TL	-	134 A8
	14.0/65 - 16	11.0	-	353	870	388	2549	STD	10	TT	-	134 A8
	14.0/65 - 16	11.0	-	353	870	388	2549	STD	14	TL	-	142 A8
Ø 17"	15.0/55 - 17	13.00	13; W13	381	850	391	2575	SPL	10	TL	-	134 A8
	15.0/55 - 17	13.00	13; W13	381	850	391	2575	STD	10	TL	-	134 A8
	15.0/55 - 17	13.00	13; W13	381	850	391	2575	STD	12	TL	-	138 A8
	15.0/55 - 17	13.00	13; W13	381	850	391	2575	STD	14	TL	-	141 A8
	15.0/55 - 17	13.00	13; W13	381	850	382	2604	STD	18	TL	-	146 A8
	15.0/55 - 17	13.00	13; W13	381	850	382	2604	STD	26	TL	-	155 A8
Ø 18"	15.0/70 - 18	13.00	13; W13	405	1010	447	3092	STD	12	TL	-	145 A8
	15.0/70 - 18	13.00	13; W13	405	1010	447	3092	STD	14	TL	-	148 A8
	15.0/70 - 18	13.00	13; W13	405	1010	447	3092	STD	16	TL	-	151 A8
Ø 20"	16.0/70 - 20	13.0	12 SDC; 13 SDC; 14	408	1075	480	3155	STD	12	TT	-	151 A8
	16.0/70 - 20	13.0	12 SDC; 13 SDC; 14	414	1085	483	3342	STD	12	TL	-	151 A8
	16.0/70 - 20	13.0	12 SDC; 13 SDC; 14	408	1075	480	3155	STD	14	TT	-	154 A8

STD: Standard - SPL: Special

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; DW = Drive Wheel; FR = Free Rolling



Bias



Performance



Durability



High Load Capacity



	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS	
		Rec.	Alt.								DW	FR
Ø 20"	16.0/70 - 20	13.0	12 SDC ; 13 SDC ; 14	408	1075	480	3155	SPL	14	TL	-	154 A8
	16.0/70 - 20	13.0	12 SDC ; 13 SDC ; 14	408	1075	480	3155	STD	14	TL	-	154 A8
	16.0/70 - 20	13.0	12 SDC ; 13 SDC ; 14	408	1075	480	3155	STD	16	TL	-	156 A8
Ø 22.5"	400/55 - 22.5	AG 11.75	12.25 ; AG 13.00	405	1016	443	3072	STD	18	TL	-	154 A8
	400/55 - 22.5	AG 11.75	12.25 ; AG 13.00	405	1016	443	3072	SR	20	TL	-	156 A8

STD: Standard - SR: Stubble Resistant - SPL: Special



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; DW = Drive Wheel; FR = Free Rolling