



## FORESTLAND

### Description

FORESTLAND is BKT's latest and innovative agro-forestry pattern. This bias tire has been specifically designed for heavy-duty service in forestry applications but, it can also be employed in some agricultural operations such as landscaping and light mulching. Moreover, the special cut-and-chip resistant tread compound along with the strong sidewall ensure a long tire life even under the harshest operating conditions.



### UM

IS Standard

### Construction

◆ Bias

### Machinery

Agriculture ■ Tractor

Version	STANDARD
Tire Type	TT
Tyre size	18.4-38
LI/SS	155;A8

## Dimensions IS Standard

SW (IS) (mm)	467
OD (IS) (mm)	1750
SLR (IS) (mm)	813
RC (IS) (mm)	5384
Rim Rec	W 16 L
Rim Alt	W 15 L
ECE	E11-106R-008167
TRA Code	LS2

## Load Capacity (IS)

km/h / bar	2.60
40	3875
50	3550

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..