



US standard



GROWING TOGETHER

MULTIMAX

RADIAL MPT TIRES

MP 540



PRODUCT DATA SHEET



Radial



152



MULTIMAX MP 540
RADIAL MPT TIRES

MULTIMAX MP 540 has been designed by BKT for all multi-purpose vehicles. Thanks to the All Steel casing, MULTIMAX MP 540 enables to carry heavy loads during on and off road applications. In addition, its block pattern design provides outstanding stability and durability.

Technologies



Block Pattern



All Steel



M+S

Performance



Stability



Durability



High Load Capacity

	US CODE	Tire size	Type	STAR RATING	LI/SS	Version	O.D.	O.W.	SLR	RC	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	RIM	
							(In.)	(In.)	(In.)	(In.)			Rec.	Alt.
Ø 16"	94068999	315/55 R 16	TL	-	120 K / 124 F	STD	29.6	12.0	13.9	91.5	21	74	W 10 L	11
Ø 18"	94069422	335/80 R 18 (12.5 R 18)	TL	-	132 K	STD	38.8	13.4	17.6	118.1	21	125	11	-
Ø 20"	94071357	275/80 R 20 (10.5 R 20)	TL	-	134 K	STD	37.6	10.6	17.4	114.7	18	92	W 9	9
	94033539	335/80 R 20	TL	-	149 K	STD	41.1	13.4	19.4	128.3	21	131	11	-
	94069873	365/80 R 20 (14.5 R 20)	TL	-	152 K	STD	42.8	14.4	19.5	130.2	21	163	11	-
Ø 24"	94072903	405/70 R 20 (16.0/70 R 20)	TL	-	152 K	STD	42.6	15.8	19.3	129.7	25	181	13	12 ; 13 SDC
	94074600	405/70 R 24 (16.0/70 R 24)	TL	-	152 J	STD	46.2	15.8	20.9	141.2	25	207	13	-

NEWSIZE

STD: Standard



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference