



ROCK STAR IND4



Description

ROCK STAR PORT IND-4 has been specifically designed for empty container handlers and forklifts. In addition to excellent traction, the unique tread compound provides superior cut and chip resistance. ROCK STAR PORT IND-4 ensures outstanding load capacity and extraordinary durability.

UM

IS Standard

Construction

◆ Bias

Machinery

Industrial & Construction ■

Version	PORT INDUSTRIAL
Tire Type	TL
Tyre size	14.00-24
LI/SS	

Dimensions IS Standard

OD (IS) (mm)	1425
SLR (IS) (mm)	635
RC (IS) (mm)	4350
Rim Rec	10.00 WA
Rim Alt	10.00 VA
TRA Code	IND4

Load Capacity (IS)

km/h / bar	10.00
10	14175

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..