



IS standard



GROWING TOGETHER

# RIB 774 (C)



PRODUCT DATA SHEET



Bias



Performance



Durability



High Load Capacity



# RIB 774 (C)

RIB 774 (C) is a low-section and narrow-width implement tire. It is ideal for hay harvesting and transport applications with balers and trailers, both on- and off-the-road. It features great load capacity and a long tire life-cycle.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS	
		Rec.	Alt.								DW	FR
<b>Ø 17"</b>	<b>19.0/45 - 17</b>	16.00	-	455	845	387	2518	STD	10	TL	-	138A8
<b>Ø 17.5"</b>	<b>215/75 - 17.5</b>	6.75	-	220	775	360	2310	STD	12	TL	-	134A8
	<b>215/75 - 17.5</b>	6.75	-	220	775	360	2310	STD	16	TL	-	139A8
	<b>225/75 - 17.5</b>	6.75	-	220	775	360	2310	STD	12	TL	-	134A8
	<b>225/75 - 17.5</b>	6.75	-	220	775	360	2310	STD	16	TL	-	139A8

STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; DW = Drive Wheel; FR = Free Rolling