



## FARM 2000

### Description

The FARM 2000 tire is suitable on tractors for soil tillage and transport applications. It is the ideal tire for heavy-duty use and in all operating conditions where good traction is required.

### UM

IS Standard

### Construction

 Bias

### Machinery

Agriculture ▪ Tractor



Version	STANDARD
Tire Type	TL
Tyre size	250/80-18
LI/SS	

## Dimensions IS Standard

SW (IS) (mm)	240
OD (IS) (mm)	870
SLR (IS) (mm)	394
RC (IS) (mm)	2679
Rim Rec	W 8
Rim Alt	W7; W9
ECE	E11-106R-003519
TRA Code	R1

## Load Capacity (IS)

km/h / bar	2.80
10 FR	2450
25 FR	2085
30 FR	1960
40 FR	1750
10 DW	1700
25 DW	1445
30 DW	1360
40 DW	1215

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..