



## F 240

### Description

F 240 is a forestry tire designed for logging applications. Its tread pattern provides excellent traction, self-cleaning properties in addition to good steering. The superior tread compound ensures extraordinary cut-and-wear resistance resulting in a longer service life. F 240 shows a large contact area for better stability.

### UM

IS Standard

### Construction

 Bias

### Machinery

Agriculture ■ Log Skidder



Version	STANDARD
Tire Type	TT
Tyre size	18-15.5
LI/SS	

## Dimensions IS Standard

SW (IS) (mm)	450
OD (IS) (mm)	990
SLR (IS) (mm)	430
RC (IS) (mm)	2930
Rim Rec	AG 13.00
ECE	E11-106R-004259
TRA Code	LS2

## Load Capacity (IS)

km/h / bar	3.50
30	4185

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..