



## TR 882

### Description

TR 882 is a very versatile tire suitable for several applications and vehicles. It has been designed to fit implement machinery, hay harvesters/balers and sugar cane machinery. Engineered with a special compound to reduce damage, this tire features also great durability and traction in every field condition. TR 882 is also available as "aramid-belted", "HD" and "special" versions to meet specific end user requirements.



### UM

US Standard

### Construction

◆ Bias

### Machinery

Agriculture ■ Baler, Industrial & Construction ■ Trailer

Version ARAMID BELTED HD

Tire Type TL

Tyre size 400/60-15.5

LI/SS

## Dimensions US Standard

USA Code	94048304
SW (US) (in)	15.7
OD (US) (in)	34.4
SLR (US) (in)	14.9
RC (US) (in)	102.6
Rim Rec	AG 13.00
ECE	E11-106R-005354

## Load Capacity (US)

mph / psi	65
5 FR	10030
15 FR	8530
20 FR	8020
25 FR	7160
5 DW	7100
15 DW	6030
20 DW	5680
25 DW	5070

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..