



IS standard



GROWING TOGETHER

TR 144



PRODUCT DATA SHEET



Bias

R-1

A6

104

Performance



High Load Capacity



Traction



TR 144

🇬🇧 TR 144 is suitable to equip small tractors to be used in soil tillage operations. TR 144 ensures outstanding performance in all operating conditions which require excellent traction with high loads. It is also available in a "special" version, which is best suitable for heavy-duty service.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 16"	7 - 16	6 L ; 6 LB ; 6.00 F	-	183	740	344	2223	STD	4	TT	75 A6
	7 - 16	6 L ; 6 LB ; 6.00 F	-	183	740	344	2223	STD	4	TL	75 A6
	7 - 16	6 L ; 6 LB ; 6.00 F	-	183	740	347	2253	STD	6	TT	84 A6
	8 - 16	6 L ; 6 LB ; 6.00 F	-	200	785	358	2342	STD	4	TT	83 A6
	8 - 16	6 L ; 6 LB ; 6.00 F	-	200	785	358	2342	HD	6	TT	91 A6
	8 - 16	6 L ; 6 LB ; 6.00 F	-	200	785	358	2342	STD	6	TT	91 A6
	8 - 16	6 L ; 6 LB ; 6.00 F	-	200	785	358	2342	STD	6	TL	91 A6
	8 - 16	6 L ; 6 LB ; 6.00 F	-	200	785	358	2342	SPL	6	TT	91 A6
	8 - 16	6 L ; 6 LB ; 6.00 F	-	200	785	358	2342	STD	8	TT	98 A6
	9.5 - 16	W 8 L	8 LB	245	850	388	2558	STD	6	TT	96 A6
	9.5 - 16	W 8 L	8 LB	245	850	388	2558	STD	6	TL	96 A6
	9.5 - 16	W 8 L	8 LB	245	850	388	2558	STD	8	TT	102 A6
9.5 - 16	W 8 L	8 LB	245	850	388	2558	STD	8	TL	102 A6	

STD: Standard - SPL: Special - HD: Heavy Duty

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference



Bias



Performance



High Load Capacity



Traction



	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 18"	8 - 18	W 6	W 7 ; 5.50 F	195	840	385	2509	STD	4	TT	85 A6
	8 - 18	W 6	W 7 ; 5.50 F	195	840	385	2509	STD	6	TT	94 A6
	8 - 18	W 6	W 7 ; 5.50 F	195	840	391	2535	SPL	6	TT	94 A6
	8 - 18	W 6	W 7 ; 5.50 F	195	840	385	2509	STD	8	TT	100 A6
	8 - 18	W 6	W 7 ; 5.50 F	195	840	391	2535	SPL	8	TT	100 A6
Ø 20"	8.3 - 20	W 7	W 6	211	890	414	2670	STD	6	TT	96 A6
	8.3 - 20	W 7	W 6	211	890	414	2670	HD	6	TT	96 A6
Ø 22"	9.5 - 22	W 8	W 7	235	1000	464	3008	STD	6	TT	104 A6

STD: Standard - SPL: Special - HD: Heavy Duty



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference