



STEER FARM



Description

STEER FARM has been designed for 2WD tractors in soil tillage applications, providing excellent steering performance.

UM

IS Standard

Construction

◆ Bias

Machinery

Agriculture ■ 2WD Tractor

Version	STANDARD
Tire Type	TT
Tyre size	7.50-16
LI/SS	103;A6

Dimensions IS Standard

SW (IS) (mm)	205
OD (IS) (mm)	805
SLR (IS) (mm)	378
RC (IS) (mm)	2451
Rim Rec	5.50 F
Rim Alt	5.00 F; 5 K; 6.00 F
ECE	E11-106R-003547
TRA Code	F2

Load Capacity (IS)

km/h / bar	3.70
30	875

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..