



IS standard



GROWING TOGETHER

# RIDEMAX

RADIAL TRANSPORT TIRES

## FL 690



PRODUCT DATA SHEET



Radial



197



# RIDEMAX FL 690

RADIAL TRANSPORT TIRES

RIDEMAX FL 690 is a radial flotation and transport tire for tank trucks and trailers. The tire is suitable for 75% on-the-road applications. As a response to the increasing demand for high loads in modern agriculture, BKT has designed this steel-belted tire withstanding very heavy loads and increasing the farmer's productivity. The low rolling resistance contributes to better fuel economy.

### Technologies



Steel Belted



Reinforced Bead



High Speed



Block Pattern

### Performance



Road Oriented



Durability



Fuel Economy

	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
Ø 26"	28 L R 26 (750/65 R 26)	176 A8/173 B	DW 25 B	DW 23 B	719	1590	695	4745	750	STD
Ø 32"	30.5 L R 32	184 A8/181 B	DH 27 B	DW 27 B	790	1800	806	5430	875	STD
	800/60 R 32	185 D	DH 27 B	DW 27 B	800	1800	817	5454	850	STD
	VF 900/65 R 32 (VF 35.5 L R 32)	197 D	DW 31 B	DW 30 ; TW 30	930	1986	838	5878	925	STD

STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; SRI = Speed Radius Index