



US standard



GROWING TOGETHER

# AW 711



PRODUCT DATA SHEET



Radial



167

**Technologies**



Steel Belted

**Performance**



Durability



Fuel Economy



High Load Capacity



Stubble Resistance



# AW 711

AW 711 is a radial implement tire specially designed for modern farming, and suitable for haulage, hay harvesting and soil tillage applications. Thanks to its special tread compound, AW 711 has an extended product life-cycle, whether it is used on soft or hard surfaces. The low rolling resistance during on-road travel ensures significant savings in fuel consumption. Thanks to the VF technology, AW 711 can carry heavy loads at low inflating pressure.

	US CODE	Tire size	LI/SS	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version
				Rec.	Alt.							
Ø 16.5"	94053292	265/70 R 16.5 (10 R 16.5)	134 A8/B	8.25	-	10.4	30.4	13.5	90.0	12	56	SR
	94053506	305/70 R 16.5 (12 R 16.5)	148 A8/B	9.75	-	12.8	33.5	14.6	100.5	13	76	SR
	94044788	340/60 R 16.5	145 A8/B	11	-	12.8	32.3	14.5	97.5	11	85	SR
	94044757	380/55 R 16.5	150 A8/B	12	11.75	14.2	32.7	14.6	98.4	11	86	SR
	94053469	395/55 R 16.5	152 A8/B	12	-	15.5	33.0	14.4	99.1	14	91	SR
	94055814	VF 410/50 R 16.5	153 B	AG 11.75	-	16.1	32.9	13.8	98.9	11	102	SB
Ø 17"	94051434	VF 480/45 R 17	167 A8/B	16.00	-	19.3	34.1	14.3	104.1	11	119	SB
Ø 18"	94053476	IF 340/65 R 18	153 A8/B	W 11	-	13.0	35.4	15.0	106.4	11	82	SR
	94045235	400/60 R 18	159 A8/B	14	13	15.5	37.2	16.5	110.5	11	118	SR
	94044924	440/55 R 18	159 A8/B	14	13	16.1	37.2	17.0	113.9	11	123	SR
Ø 19.5"	94044931	15 R 19.5	139 D	11.75	12.75	15.3	40.1	18.5	121.8	16	139	SR
	94066605	380/70 R 19.5	159 A8/B	12.15	13.15	15.3	40.1	17.5	119.6	16	139	SR

SR: Stubble Resistant - SB: Steel Belted

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference