



US standard



GROWING TOGETHER

XL GRIP (L3)



PRODUCT DATA SHEET



Bias

E-3/L-3



XL GRIP (L3)

XL GRIP (E-3/L-3) is a wide-base bias-ply tire for loaders designed to minimize cuts and punctures in heavy-duty loading applications. It provides exceptional traction as well as an extended tire life.

Performance



Cut Resistance



Durability



Heavy Duty



Stability



Traction

	US CODE	Tire size	Type	PR	LI/SS	Version	O.D. (In.)	O.W. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	RIM	
													Rec.	Alt.
Ø 20"	94030538	16.0/70 - 20	TL	16	-	STD	42.9	15.9	18.9	129.7	33	153	13 SDC	-
Ø 25"	94051182	15.5 - 25	TL	12	-	STD	50.6	15.8	22.6	148.3	32	190	12.00/1.3	12.00/1.3 (DC)
	94040650	17.5 - 25	TL	12	-	STD	53.0	17.1	24.5	156.7	38	280	14.00/1.5	-
	94015719	17.5 - 25	TL	16	-	STD	53.0	17.1	24.5	156.7	38	284	14.00/1.5	-
	94031351	17.5 - 25	TL	20	-	DB	53.0	17.1	24.5	156.7	38	321	14.00/1.5	-
	94015740	17.5 - 25	TL	20	-	STD	53.0	17.1	24.5	156.7	38	304	14.00/1.5	-
	94051830	17.5 - 25	TT	20	-	DB	53.0	17.1	24.5	156.7	38	297	14.00/1.5	-
	94063406	17.5 - 25	TL	24	-	DB	53.0	17.1	24.5	156.7	38	324	14.00/1.5	-
	94040667	20.5 - 25	TL	12	-	STD	58.5	20.9	26.9	173.0	41	391	17.00/2.0	-
	94015832	20.5 - 25	TL	16	-	STD	58.5	20.9	26.9	173.0	41	416	17.00/2.0	-
	94015856	20.5 - 25	TL	20	-	STD	58.5	20.9	26.9	173.0	41	434	17.00/2.0	-
	94032235	20.5 - 25	TL	24	-	STD	58.5	20.9	26.9	173.0	41	453	17.00/2.0	-
	94015863	23.5 - 25	TL	16	-	STD	64.0	23.6	29.2	189.4	45	569	19.50/2.5	-
	94015870	23.5 - 25	TL	20	-	STD	64.0	23.6	29.2	189.4	45	601	19.50/2.5	-
94015894	23.5 - 25	TL	24	-	STD	64.0	23.6	29.2	189.4	45	626	19.50/2.5	-	

STD: Standard - DB: Dual Bead

Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference



Bias

E-3/L-3

Performance



Cut Resistance



Durability



Heavy Duty



Stability



Traction



	US CODE	Tire size	Type	PR	LI/SS	Version	O.D. (In.)	O.W. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	RIM	
													Rec.	Alt.
Ø 25"	94054107	23.5 - 25	TL	24	-	AB HD	64.0	23.6	29.2	189.4	45	626	19.50/2.5	-
	94040674	26.5 - 25	TL	20	-	STD	68.5	26.8	31.3	202.8	46	737	22.00/3.0	-
	94015900	26.5 - 25	TL	28	-	STD	68.5	26.8	31.3	202.8	46	816	22.00/3.0	-
	94027989	26.5 - 25	TL	32	-	STD	68.5	26.8	31.3	202.8	46	853	22.00/3.0	-
	94015917	29.5 - 25	TL	28	-	STD	73.2	29.9	33.4	218.3	49	988	25.00/3.5	-
	94029594	29.5 - 25	TL	32	-	STD	73.2	29.9	33.4	218.3	49	1025	25.00/3.5	-

STD: Standard - AB HD: Aramid Belted Heavy Duty



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference