



US standard



GROWING TOGETHER

SKID POWER



PRODUCT DATA SHEET



Bias



141



SKID POWER

SKID POWER has been designed for skid steers in construction applications. It shows excellent traction as well as enhanced self-cleaning features. The tire features an extra deep tread along with extra sidewall protection providing excellent cut and chip resistance and outstanding durability. SKID POWER is the ideal tire for loose surfaces.

Performance



Cut and Chip Resistance



Self-Cleaning



Traction

	US CODE	Tire size	Type	PR	LI/SS		Version	O.D. (In.)	S.W. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	RIM	
					DW	FR								Rec.	Alt.
Ø 12"	94076093	23 X 10.5 - 12	TL	6	90 A8	90 A8	IMP	23.2	10.4	-	-	17	29	8.5 I - 55	7.00 I - 55 ; I - 70 ; I - 90
Ø 14"	94042050	25 X 8.5 - 14	TL	6	-	-	STD	25.7	8.4	12.0	75.3	17	24	7 JA	-
Ø 16.5"	94055661	10 - 16.5	TL	8	116 A8	-	IMP	30.5	10.0	14.0	90.0	19	44	8.25	-
	94017102	10 - 16.5	TL	8	-	-	STD	30.5	10.0	14.0	90.0	19	44	8.25	-
	94041008	10 - 16.5	TL	10	-	-	STD	30.5	10.0	14.0	90.0	19	44	8.25	-
	94055678	12 - 16.5	TL	10	125 A8	-	IMP	32.3	12.0	14.7	95.4	22	58	9.75	-
	94017133	12 - 16.5	TL	10	-	-	STD	32.3	12.0	14.7	95.4	22	58	9.75	-
Ø 17.5"	94056125	14 - 17.5	TL	14	141 A8	-	IMP	37.0	14.0	16.7	109.2	25	101	10.5	-
	94017164	14 - 17.5	TL	14	-	-	STD	37.0	14.0	16.7	109.2	25	101	10.5	-

STD: Standard - IMP: Implement



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference