



FL 639

Description

FL 639 is a field-oriented flotation radial tire also suitable for spreading applications. Its wide footprint area ensures low soil compaction resulting in increased crop productivity. The reinforced bead and the sidewall protection contribute to an extended tire life-cycle. FL 639 ensures extraordinary traction along with great self-cleaning properties.

UM

IS Standard

Construction

 Radial

Machinery

Agriculture ■ Spreader



Version

STANDARD

Tire Type

TL

Tyre size

600/50R22.5

LI/SS

159;D

Dimensions IS Standard

| | |
|---------------|----------------|
| SW (IS) (mm) | 611 |
| OD (IS) (mm) | 1172 |
| SLR (IS) (mm) | 530 |
| RC (IS) (mm) | 3540 |
| Rim Rec | AG 20.00 |
| ECE | E4-106R-000802 |

Load Capacity (IS)

| km/h / bar | 0.8 | 1.0 | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.6 | 4.0 |
|------------|------|------|------|------|------|------|------|------|------|------|
| 70 | 1280 | 1480 | 1675 | 2020 | 2355 | 2680 | 3020 | 3330 | 3670 | 3985 |
| 65 | 1400 | 1620 | 1840 | 2220 | 2585 | 2950 | 3310 | 3660 | 4025 | 4375 |
| 50 | 1695 | 1960 | 2225 | 2700 | 3125 | 3575 | 4000 | 4420 | 4875 | 5295 |
| 40 | 1920 | 2220 | 2520 | 3040 | 3540 | 4050 | 4555 | 5020 | 5520 | 6000 |
| 25 | 2215 | 2560 | 2905 | 3510 | 4080 | 4675 | 5210 | 5800 | 6365 | 6915 |
| 10 | 2520 | 2915 | 3310 | 4000 | 4650 | 5325 | 5940 | 6600 | 7245 | 7875 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..