



SM 55 L5S

Description

SM 55 (L-5S) is a bias-ply tyre ideal for underground mining operations. The specially designed cut-and-chip-resistant tread compound minimizes punctures thereby reducing machine downtime. The extra-deep L-5 S tread depth guarantees an extended tyre life. The tyre is also available in a steel-belted version.

UM

IS Standard

Construction

◆ Bias

Machinery

OTR ■ Underground Mining Vehicle



Version	STEEL BELTED
Tyre Type	TL
Tyre size	26.5-25
LI/SS	

Dimensions IS Standard

OD (mm)	1798
SLR (mm)	816
RC (mm)	5322
Rim Rec	22.00/3.0
TRA Code	L55

Load Capacity (IS)

km/h / bar	4.75
10	15500
15	13485
25	12400

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21-03-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..