



US standard



GROWING TOGETHER

AGRIMAX

RADIAL TRACTOR TIRES

RT 765M



PRODUCT DATA SHEET



Radial



Technologies



High Speed



Steel Belted

Performance



Traction



Self-Cleaning



Reduced Soil Compaction



High Load Capacity



Handling and Comfort



AGRIMAX RT 765M

RADIAL TRACTOR TIRES

AGRIMAX RT 765M, a BKT 70 series tire, is suitable for cutting-edge tractors for several heavy-duty applications such as soil tillage, field and road transport, vineyard harvesting, and spraying. A wide contact patch ensures the best possible traction and comfort on all surfaces at any time. This tire provides great self-cleaning properties and reduced soil compaction. Two sizes are available with steel-belted technology.

	US CODE	Tire size	LI/SS	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version
				Rec.	Alt.							
Ø 38"	94066803	710/70 R 38	175D/ 178A8	DW 23 B	DW 25 B	28.2	77.1	33.8	226.4	74	672	STD
	94066797	710/70 R 38	171D/ 174A8	DW 23 B	-	28.2	77.1	33.8	226.4	74	672	STD
	94066773	710/70 R 38	166 D	DW 23 B	DW 25 B	28.2	77.1	33.8	226.4	74	632	STD
	94066810	710/70 R 38	175D/ 178A8	DW 23 B	-	28.2	77.1	33.8	226.4	74	674	SPL
	94066780	710/70 R 38	166 D	DW 23 B	DW 25 B	28.2	77.1	33.8	226.4	74	634	SPL
Ø 42"	94066469	710/70 R 42	176D/ 179A8	DW 23 B	DW 25 B	28.2	81.1	36.3	243.1	74	724	STD
	94066452	710/70 R 42	173D/ 176A8	DW 23 B	DW 25 B	28.2	81.1	36.3	243.1	74	708	STD
	94066476	710/70 R 42	173D/ 176A8	DW 23 B	DW 25 B	28.2	81.1	36.3	243.1	74	718	SPL
	94066483	710/70 R 42	176 D/ 179A8	DW 23 B	DW 25 B	28.2	81.1	36.3	243.1	74	734	SPL

STD: Standard - SPL: Special



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference