



## AGRIMAX RT 955



### Description

AGRIMAX RT 955 is a BKT radial tire for row crop applications, while some sizes are also suitable for spraying and vineyards. The special tread design with a rounded shoulder provides excellent traction performance, stability and self-cleaning properties. Thanks to its strong casing, AGRIMAX RT 955 has a high load capacity.

### UM

IS Standard

### Construction

 Radial

### Machinery

Agriculture ■ Sprayer

Version	STANDARD
Tire Type	TL
Tyre size	270/95R44
LI/SS	142;A8/B

## Dimensions IS Standard

SW (IS) (mm)	275
OD (IS) (mm)	1632
SLR (IS) (mm)	764
RC (IS) (mm)	4983
Rim Rec	W 9
Rim Alt	W 8; W 10
ECE	E4-106R-00784
TRA Code	R1

## Load Capacity (IS)

km/h / bar	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.4
50	1035	1355	1645	1805	1910	2095	2280	2465	2650	-
40	1035	1355	1645	1805	1910	2095	2280	2465	2650	-
30	1110	1450	1765	1935	2045	2245	2445	2645	2840	-
10	1235	1555	1910	2270	2625	2705	3025	3340	3660	3975

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..