



US standard



GROWING TOGETHER

I-1



PRODUCT DATA SHEET



Bias



145



I-1

I-1 has been designed for field and road transport as well as for soil tillage operations with implements and trailers. I-1 is a high-speed tire that optimizes travel times so that you can focus on your core business. The special tread design ensures a long service life also in harsh conditions and if there is stubble in the fields.

Technologies



High Speed

Performance



Durability



Stubble Resistance

	US CODE	Tire size	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version	PR	Type	LI/SS	
			Rec.	Alt.										DW	FR
Ø 14"	94006120	9.5 L - 14 SL	7.00	8 KB	9.3	29.3	12.8	84.8	9	28	STD	8	TL	111 D	
	94006113	9.5 L - 14 SL	7.00	8 KB	9.3	29.3	12.8	84.8	9	26	STD	8	TT	111 D	
	94035359	11 L - 14 SL	8.00	8 KB	10.1	29.6	13.1	86.9	10	32	STD	8	TL	112 D	
Ø 15"	94045204	6.70 - 15 SL	4½ KB	5 KB	6.8	28.0	12.6	81.9	7	19	STD	6	TL	97 D	
	94006083	6.70 - 15 SL	4½ KB	5 KB	6.8	28.0	12.6	81.9	7	17	STD	6	TT	97 D	
	94005734	6.70 - 15 SL	4½ KB	5 KB	6.8	28	12.6	81.9	7	20	STD	8	TT	102 D	
	94039838	7.60 - 15 SL	5.50	6 LB	7.6	28.9	12.9	84.7	8	23	STD	6	TT	100 D	
	94056996	7.60 - 15 SL	5.50	6 LB	7.6	28.9	12.9	84.7	8	28	STD	8	TL	106 D	
	94039845	7.60 - 15 SL	5.50	6 LB	7.6	28.9	12.9	84.7	8	25	STD	8	TT	106 D	
	94048458	7.60 - 15 SL	5.50	6 LB	7.6	28.9	12.9	84.7	8	29	STD	10	TL	110 D	
	94034819	7.60 - 15 SL	5.50	6 LB	7.6	28.9	12.9	84.7	8	26	STD	10	TT	110 D	
	94028481	9.5 L - 15 SL	7.00	8 LB	9.5	30.1	13.4	88.3	9	28	STD	6	TT	105 D	
	94006151	9.5 L - 15 SL	7.00	8 LB	9.5	30.1	13.4	88.3	9	31	STD	8	TL	112 D	
	94044498	9.5 L - 15 SL	7.00	8 LB	9.5	30.1	13.4	88.3	9	33	SR	8	TL	112 D	
	94006144	9.5 L - 15 SL	7.00	8 LB	9.5	30.1	13.4	88.3	9	29	STD	8	TT	112 D	

SR: Stubble Resistant - STD: Standard

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; DW = Drive Wheel; FR = Free Rolling



Bias



145



Technologies



High Speed

Performance



Durability



Stubble Resistance

	US CODE	Tire size	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version	PR	Type	LI/SS	
			Rec.	Alt.										DW	FR
Ø 15"	94006175	9.5 L - 15 SL	7.00	8 LB	9.5	30.1	13.4	88.3	9	34	STD	12	TL	121 D	
	94045174	9.5 L - 15 SL	7.00	8 LB	9.5	30.1	13.4	88.3	9	36	SR	12	TL	121 D	
	94005871	11 L - 15 SL	8 LB	10 LB	10.6	30.3	13.5	88.8	10	34	STD	8	TL	113 D	
	94044801	11 L - 15 SL	8 LB	10 LB	10.6	30.3	13.5	88.8	10	36	SR	8	TL	113 D	
	94005864	11 L - 15 SL	8 LB	10 LB	10.6	30.3	13.5	88.8	10	31	STD	8	TT	113 D	
	94005901	11 L - 15 SL	8 LB	10 LB	10.6	30.3	13.5	88.8	10	36	STD	10	TL	118 D	
	94005895	11 L - 15 SL	8 LB	10 LB	10.6	30.3	13.5	88.8	10	34	STD	10	TT	118 D	
	94026197	11 L - 15 SL	8 LB	10 LB	10.6	30.3	13.5	88.8	10	36	STD	12	TL	121 D	
	94044818	11 L - 15 SL	8 LB	10 LB	10.6	30.3	13.5	88.8	10	40	SR	12	TL	121 D	
	94005970	12.5 L - 15 SL	10 LB	-	12.2	32.3	14.3	94.6	11	46	STD	8	TL	119 D	
	94005963	12.5 L - 15 SL	10 LB	-	12.2	32.3	14.3	94.6	11	43	STD	8	TT	119 D	
	94005994	12.5 L - 15 SL	10 LB	-	12.2	32.3	14.3	94.6	11	46	STD	10	TL	-	
	94005987	12.5 L - 15 SL	10 LB	-	12.2	32.3	14.3	94.6	11	43	STD	10	TT	123 D	
	94006038	12.5 L - 15 SL	10 LB	-	12.2	32.3	14.3	94.6	11	47	STD	12	TL	-	
	94044825	12.5 L - 15 SL	10 LB	-	12.2	32.3	14.3	94.6	11	52	SR	12	TL	-	

SR: Stubble Resistant - STD: Standard

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; DW = Drive Wheel; FR = Free Rolling



Bias



145



Technologies



High Speed

Performance



Durability



Stubble Resistance

	US CODE	Tire size	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version	PR	Type	LI/SS	
			Rec.	Alt.										DW	FR
Ø 15"	94006021	12.5 L - 15 SL	10 LB	-	12.2	32.3	14.3	94.6	11	42	STD	12	TT	-	-
Ø 15.3"	94065219	10.0/75 - 15.3	9.00	-	10.6	30.1	14.1	88.0	11	38	STD	12	TL	-	118 D
	94065202	10.0/75 - 15.3	9.00	-	10.6	30.1	-	-	11	36	STD	12	TT	-	118 D
Ø 16"	94030910	7.50 - 16 SL	5.50 F	6 LB	8.1	30.9	13.8	90.6	7	28	SPL	8	TT	-	-
	94006090	7.50 - 16 SL	5.50 F	6 LB	8.1	30.9	13.8	90.6	7	28	STD	8	TT	-	-
	94041534	7.50 - 16 SL	5.50 F	6 LB	8.1	30.9	13.8	90.6	7	28	SPL	10	TT	-	-
	94053308	7.50 - 16 SL	5.50 F	6 LB	8.1	30.9	13.8	90.6	7	28	STD	10	TT	-	-
	94049394	9.00 - 16 SL	6 LB	8 LB; W 8 L	9.2	33.3	14.7	97.5	9	42	STD	10	TL	-	-
	94006106	9.00 - 16 SL	6 LB	8 LB; W 8 L	9.2	33.3	14.7	97.5	9	39	STD	10	TT	-	-
	94005925	11 L - 16 SL	8 LB	10 LB; W 8 L	10.6	31.3	14.0	91.7	10	32	STD	8	TT	-	-
	94005949	11 L - 16 SL	8 LB	10 LB; W 8 L	10.6	31.3	14.0	91.7	10	35	STD	10	TT	-	-
	94031405	11 L - 16 SL	8 LB	10 LB; W 8 L	10.6	31.3	14.0	91.7	10	35	STD	12	TT	-	-
	94006045	12.5 L - 16 SL	10 LB	W 10 L	12.2	33.3	14.7	97.5	11	45	STD	8	TT	-	-
	94005697	12.5 L - 16 SL	10 LB	W 10 L	12.2	33.3	14.7	97.5	11	45	STD	10	TT	-	-

STD: Standard - SPL: Special

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; DW = Drive Wheel; FR = Free Rolling



Bias



Technologies



High Speed

Performance



Durability



Stubble Resistance

	US CODE	Tire size	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version	PR	Type	LI/SS	
			Rec.	Alt.										DW	FR
Ø 16"	94041411	12.5 L - 16 SL	10 LB	W 10 L	12.2	33.3	14.7	97.5	11	48	STD	12	TL	-	-
	94006069	12.5 L - 16 SL	10 LB	W 10 L	12.2	33.3	14.7	97.5	11	46	STD	12	TT	-	-
	94048205	12.5 L - 16 SL	10 LB	W 10 L	12.2	33.3	14.7	97.5	11	53	SR	14	TL	-	-
Ø 16.1"	94035403	14 L - 16.1 SL	W 11 C	-	14.2	36.8	16.1	107.9	13	76	STD	8	TL	-	-
	94034000	14 L - 16.1 SL	W 11 C	-	14.2	36.8	16.1	107.9	13	84	STD	12	TL	-	-
	94031337	16.5 L - 16.1 SL	W 14 C	W 14 CH	17.1	40.4	17.5	118.2	14	108	STD	10	TL	138 D	-
	94055128	16.5 L - 16.1 SL	W 14 C	W 14 CH	17.1	40.4	17.5	118.2	14	112	STD	14	TL	145 D	-
	94032105	19 L - 16.1 SL	W 16 C	W 16 CH	19.3	43.3	18.7	126.9	17	133	STD	10	TL	-	-
	94041428	19 L - 16.1 SL	W 16 C	W 16 CH	19.3	43.3	18.7	126.9	17	134	STD	12	TL	-	-
	94035311	19 L - 16.1 SL	W 16 C	W 16 CH	19.3	43.3	18.7	126.9	17	147	STD	14	TL	-	-
	94064304	21.5 L - 16.1 SL	W 18 CH	W 16 CH	22.4	45.3	19.5	138.2	19	174	SR	8	TL	143 D	-
	94039944	21.5 L - 16.1 SL	W 18 CH	W 16 CH	22.4	45.3	19.5	138.2	19	169	STD	8	TL	-	-
	94032341	21.5 L - 16.1 SL	W 18 CH	W 16 CH	22.4	45.3	19.5	138.2	19	187	STD	14	TL	-	-
94052738	21.5 L - 16.1 SL	W 18 CH	W 16 CH	22.4	45.3	19.5	138.2	19	187	STD	18	TL	-	-	

STD: Standard - SR: Stubble Resistant

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; DW = Drive Wheel; FR = Free Rolling



Bias



145

Technologies



High Speed

Performance



Durability



Stubble Resistance



	US CODE	Tire size	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version	PR	Type	LI/SS	
			Rec.	Alt.										DW	FR
Ø 18"	94057146	10.5/80 - 18	W 9	W 8 ; 9	11.0	35.0	16.4	105.5	13	58	STD	12	TT	-	135 A8
Ø 24"	94045631	9.00 - 24 SL	W 8 H	-	10.7	43.1	-	-	10	74	SR	8	TL	-	-
	94045648	11.25 - 24 SL	W 10 H	W 10 ; W 8	12.8	46.1	-	-	11	97	STD	8	TL	-	-

STD: Standard - SR: Stubble Resistant



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; DW = Drive Wheel; FR = Free Rolling