



AW 705

Description

AW 705 has been developed for implement machinery, trailers and balers in soil tillage and haulage applications. It is ideal for modern farming thanks to improved durability and high load capacity.

UM

IS Standard

Construction

◆ Bias

Machinery

Agriculture ■ Baler



Version	STANDARD
Tyre Type	TL
Tyre size	15.0/55-17
LI/SS	

Dimensions IS Standard

SW (mm)	381
OD (mm)	850
SLR (mm)	391
RC (mm)	2575
Rim Rec	13.00
Rim Alt	13; W 13
ECE	E4-106R-001547

Load Capacity (IS)

km/h / bar	3.60
10 FR	3605
25 FR	3065
30 FR	2885
40 FR	2575

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21-03-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..