



US standard



GROWING TOGETHER

EARTHMAX

RADIAL OTR TIRES

SR 452



PRODUCT DATA SHEET



Radial



EARTHMAX SR 452

RADIAL OTR TIRES



EARTHMAX SR 452 is an All Steel radial tire specifically designed for Rigid Dump Trucks in transport operations. Its unique E-4 deep tread pattern stands for excellent traction and exceptional heat resistance, minimizing vibration and noise to provide best handling and comfort. Its strong steel casing and belts provide excellent stability and resistance to cuts and punctures. EARTHMAX SR 452 features a squared shoulder that maximizes ground contact for excellent maneuverability.

Technologies



All Steel



Steel Belted

Performance



Cut and Chip Resistance



Handling and Comfort



Heat Resistance



Stability



Steering Control



Traction

| | US CODE | Tire size | Type | STAR RATING | LI/SS | Version | TRA CODE | TMPH | O.D. | O.W. | SLR | RC | TREAD DEPTH (32nds) | TIRE WEIGHT (lbs) | RIM | |
|-------------------|----------|------------|------|-------------|-------|---------|----------|------|-------|-------|-------|-------|---------------------|-------------------|-----------|------|
| | | | | | | | | | (In.) | (In.) | (In.) | (In.) | | | Rec. | Alt. |
| \varnothing 35" | 94063383 | 24.00 R 35 | TL | ** | 209 B | CRC | E-4 | 243 | 85.4 | 26.0 | 39.2 | 264.9 | 71 | 1602 | 17.00/3.5 | - |
| | 94063833 | 24.00 R 35 | TL | ** | 209 B | STDC | E-4 | 284 | 85.4 | 26.0 | 39.2 | 264.9 | 71 | 1588 | 17.00/3.5 | - |
| | 94063970 | 24.00 R 35 | TL | *** | 212 B | CRC | E-4 | 243 | 85.4 | 26.0 | 39.2 | 264.9 | 71 | 1691 | 17.00/3.5 | - |
| | 94063987 | 24.00 R 35 | TL | *** | 212 B | STDC | E-4 | 284 | 85.4 | 26.0 | 39.2 | 264.9 | 71 | 1678 | 17.00/3.5 | - |

CRC: Cut Resistance Compound - STDC: Standard Compound



Tolerances: O.D. \pm 2% - O.W. \pm 2% - RC \pm 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference