



## MULTIMAX MP 515

### Description

MULTIMAX MP 515 is an agro-industrial radial tire designed for universal vehicles and fertilizer trucks. It is suitable for municipality and transport applications. The tire shows a unique tread design providing superior riding comfort on the road as well as excellent self-cleaning properties and great traction. The strong steel-belted nylon casing and the reinforced shoulder ensure extraordinary durability. MULTIMAX MP 515 is the perfect tire also at high speeds (90km/h).



### UM

US Standard

### Construction

 Radial

### Machinery

Agriculture ■ Universal Vehicle

Version	STANDARD
Tire Type	TL
Tyre size	405/70R20MPT
LI/SS	136;G

## Dimensions US Standard

USA Code	94056545
SW (US) (in)	16.0
OD (US) (in)	42.4
SLR (US) (in)	19.4
RC (US) (in)	129.4
Rim Rec	13
Rim Alt	13 SDC; 12 SDC; 11 SDC; 11
ECE	E4-54R-0016565

## Load Capacity (US)

mph / psi	23	29	36	44	51
55	2950	3480	4010	4500	4940
40	3210	3780	4350	4880	5370
25	3410	4010	4620	5180	5690

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..