



IS standard



GROWING TOGETHER

ROCK GRIP IND4 (ECH)



PRODUCT DATA SHEET



Bias



ROCK GRIP IND4 (ECH)

ROCK GRIP PORT INDUSTRIAL IND-4 (ECH) is a bias-ply tire designed for Empty container handler in several applications including industrial handling and steelworks. The special ROCK GRIP compound ensure particular heat resistance along with great stability and durability.

Technologies



Special Compound

Performance



Durability



Heat Resistance



Stability

	Tire size	Type	PR	LI/SS	Version	O.W.	O.D.	SLR	RC	RIM	
						(mm)	(mm)	(mm)	(mm)	Rec.	Alt.
Ø 24"	12.00 - 24	TT	20	-	PORT IND	315	1265	595	3755	8.5	8.0
	12.00 - 24	TT	24	-	PORT IND	315	1265	595	3755	8.5	8.0
	14.00 - 24	TL	28	-	PORT IND	375	1410	647	4173	10.00 WA	10.00 VA
	14.00 - 24	TL	32	-	PORT IND	375	1410	647	4173	10.00 WA	10.00 VA
	14.00 - 24	TL	24	-	PORT IND	375	1410	647	4173	10.00 W	-
	14.00 - 24	TL	28	-	PORT IND	375	1410	647	4173	10.00 W	-
	14.00 - 24	TL	32	-	PORT IND	375	1410	647	4173	10.00 W	-
Ø 25"	16.00 - 25	TL	32	-	PORT IND	470	1525	699	4514	11.25/2.0	13.00/2.0
	16.00 - 25	TL	36	-	PORT IND	470	1525	699	4514	11.25/2.0	13.00/2.0

PORT IND: Port Industrial



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference