



AGRIMAX V-FLECTO

Description

AGRIMAX V-FLECTO is BKT's response to the challenging demand of both technology and performance for high-power tractors. This tire is perfect for soil tillage and haulage applications thanks to reduced soil compaction and self-cleaning properties. With the innovative VF technology, AGRIMAX V-FLECTO can carry heavy loads with a lower inflating pressure compared to standard and IF tires, reaching high speeds. It also features the Narrow Rim Option that allows mounting standard rims on the tire. BKT has designed this tire with optimized geometry to enhance driving comfort both in the fields and on the road reducing fuel consumption.

UM

IS Standard

Construction

Machinery

Agriculture ■ High-Power Tractor



Version

STANDARD

Tire Type

TL

Tyre size

VF710/55R34

LI/SS

170;D

Dimensions IS Standard

SW (IS) (mm)	708
OD (IS) (mm)	1659
SLR (IS) (mm)	726
RC (IS) (mm)	4910
Rim Rec	DW 25 B
Rim Alt	DW 27 B
ECE	E11-106R-0010831
TRA Code	R1W

field_1

km/h / bar	0.6	0.8	1	1.2	1.4	1.6	2								
70	2675	3110	3600	4040	4475	4910	5460								
from 65 to 40	2940	3420	3960	4440	4920	5400	6000								
30	2995	3485	4035	4525	5015	5505	6120								
20	3055	3555	4115	4615	5115	5615	6240								
10	3230	3760	4355	4880	5410	5940	6600								
*Upto 10 Cyc with front loader	4115	4785	5540	6215	6885	7560	8400								
10HT	2995	3485	4035	4525	5015	5505	6120								

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 25-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..