



## MULTIMAX MP 538



### Description

MULTIMAX MP 538 is a radial tire specifically designed for graders and loaders operating in winter conditions on ice or snow. Thanks to the strong steel-belted casing, MULTIMAX MP 538 allows to carry heavy loads at high speed and the unique tread design helps maintaining excellent traction on ice and snow.

### UM

US Standard

### Construction

 Radial

### Machinery

Agriculture ■ Telehandler, Industrial & Construction ■ Grader

Version	STEEL BELTED
Tire Type	TL
Tyre size	405/70R20MPT
LI/SS	152;G

## Dimensions US Standard

USA Code	94069682
SW (US) (in)	16.0
OD (US) (in)	42.4
SLR (US) (in)	19.1
RC (US) (in)	129.5
Rim Rec	W13

## Load Capacity (US)

mph / psi	87
55	7850
40	8500
25	9000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..