



## RIDEMAX FL 615



### Description

RIDEMAX FL 615 is a radial flotation tire suitable for non-driven wheels of trailers, tankers and spreaders. The steel-belted structure offers high puncture resistance along with increased durability and high load capacity. RIDEMAX FL 615 provides low rolling resistance on the road with outstanding self-cleaning properties in the fields. The rounded shoulder and wide footprint area ensure best soil protection.

### UM

IS Standard

### Construction

 Radial

### Machinery

Agriculture ■ Trailer

Version	STEEL BELTED
Tire Type	TL
Tyre size	VF900/65R38
LI/SS	200;D

## Dimensions IS Standard

SW (IS) (mm)	891
OD (IS) (mm)	2115
SLR (IS) (mm)	929
RC (IS) (mm)	6445
Rim Rec	DW 30 B
ECE	E11-106R-0011504

## Load Capacity (IS)

km/h / bar	1.0	1.2	1.6	2.0	2.4	2.8
65	6860	7700	9380	10640	12320	14000
50	8030	9010	10975	12450	14415	16380
40	8850	9935	12105	13730	15895	18060
30	9675	10860	13230	15005	17375	19740
25	10020	11245	13695	15535	17990	20440
20	10430	11705	14260	16175	18730	21280
10	11255	12630	15385	17450	20205	22960

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..