



## AGRIMAX PROHARVEST

### Description

AGRIMAX PROHARVEST is BKT's response to the current market needs in terms of combines and harvesting machines. The advanced VF (Very High Flexion) technology allows AGRIMAX PROHARVEST to carry 40% more load compared to standard tires with the same tire pressure minimizing soil compaction. Moreover, the three layers of steel belts combined with the cut and chip resistant compound ensure excellent puncture resistance, even on case of stubbles or crops leftovers on the field. The structure of the tire with a reinforced bead and a strong polyester carcass is synonym of durability and stability of the tire even during heavy duty operation.



### UM

IS Standard

### Construction

 Radial

### Machinery

Agriculture ■ Harvester

Version	STEEL BELTED
Tire Type	TL
Tyre size	1000/55R32
LI/SS	197;D

## Dimensions IS Standard

SW (IS) (mm)	1006
OD (IS) (mm)	1900
SLR (IS) (mm)	841
RC (IS) (mm)	5703
Rim Rec	36.00 VA (multi-piece)
ECE	E11-106R-0010574

## Load Capacity (IS)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2
70	4560	5265	5965	6785	7485	8300	9240	9940	10875	11690
from 65 to 40	5015	5785	6555	7455	8225	9125	10155	10925	11955	12850
30	5115	5900	6690	7605	8395	9310	10360	11145	12195	13110
20	5215	6015	6820	7755	8555	9490	10560	11365	12430	13365
10	5515	6365	7210	8200	9050	10040	11170	12015	13150	14135
*Upto 30 Cyc	5690	6565	7440	8460	9335	10360	11525	12400	13565	14585
*Upto 15 Cyc	6795	7840	8885	10105	11150	12365	13760	14805	16200	17415
*Upto 10 Cyc	7445	8590	9735	11070	12215	13555	15080	16225	17750	19085
10HT	5115	5900	6690	7605	8395	9310	10360	11145	12195	13110

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..